

Event CCTV

Access unrivalled visibility over long-range distances, to provide coverage you can rely on. Easy-to-use, rapid deployment and quality imagery, provides a great security addition to any site.

KEY BENEFITS:

- ✓ IP66 rated pan/tilt/zoom camera
- ✓ Good for close-range and long-range (up to 250m/820ft) viewing
- ✓ Built-in OptimizedIR (Infra-Red) for clear, low-light viewing
- ✓ Option of larger SRL SolarPLUS® panels to provide up to 24/7/365 runtime
- ✓ Multiple cameras can be configured to create a single, scalable system
- ✓ 4G connectivity using multi-network roaming SIM (EE, 3, O2 & VODA)
- ✓ Easy setup with one button operation

FUNCTIONALITY:

- i Up to 2992p (4K) resolution
- i 32x optical zoom
- i 12x digital zoom
- i Extend up to 6.5m with hand-wound mast
- i Core and additional analytics included
- i Web and mobile based access
- i Four adjustable legs to suit all terrains
- i Four bullet locks & security tracker fitted

RELATED PRODUCTS:

- 🔗 Haul Route PLUS®
- 🔗 SRL SolarPLUS®
- 🔗 Portable ANPR
- 🔗 SRL Telematics



AVAILABLE TO HIRE OR PURCHASE

E cctv@srl.co.uk T 0808 2818 775 W srl.co.uk

Scan here for more
Event CCTV information



PHYSICAL APPEARANCE	
Transport Height	2300mm
Deployed Height	Up to 6500mm
Box Dimensions	825mm (H) x 575mm (W) x 920mm (D)
Overall Dimensions	6500mm (H) x 700mm (W) x 965mm (D)
Footprint (legs)	1170mm (W) x 1310mm (D)
Weight (exc. batteries)	TBC
Weight (inc. batteries)	TBC
Deployment	Manual lifting aid required
Vandal Rating	IK10
IP Rating	IP66
Security	Four integrated bullet locks and tracker fitted with motion alarm & battery alerts

POWER	
Battery Type	AGM
Run Time	Up to 14 Days (AGM)
Battery Capacity	100 mAh (AGM) / per battery
No. of Batteries	6
Charge Time	8 hours
SRL Solar PLUS® Compatible	Yes
Operating Voltage	12v
Operating Current	19w
Operating Temperature	-40°C / + 50°C

COMMUNICATION	
Connectivity	4G roaming multi-network SIM via integrated router (EE, 3, O2 & VODA)
Authentication	Multi-level encrypted communication
SRL Telematics	Yes

SOLAR TECHNOLOGY	
SRL Solar PLUS® Power	50w
Intergrated MPPT (Maximum Power Point Tracking) Charge Controller	Yes
Cell Technology	Monocrystalline silicon
Conversion of Sunlight	24%
Safety Class	A
Larger Solar Panels	Yes (optional) - Improve running time up to 24/7, 365 days a year

CAMERA	
Camera Type	Pan / Tilt / Zoom
Image Sensor	Starlight CMOS (Metal-Oxide Semiconductor)
Day and Night	Automatic (OptimizedIR)
Image Stabilisation	Yes
Resolution	2992p x 2992p (4K) to 160p x 160p
Frame Rate	Up to 50/60fps (50/60 Hz)
Zoom	32x Optical / 12x Digital (384x Total)
Range	Up to 250m (820ft)
Zip-Stream Technology	Yes - reduce bandwidth by up 50%
ControlHub	Yes
Image Storage	Site incidents are captured and stored for up to 30 days for auditing purposes

ANALYTICS	
Video Motion Detection	Yes
Motion Guard	Yes
Fence Guard	Yes
Loitering Guard	Yes
VMD Person Detection	Yes
VMD Vehicle Detection	Yes
Autotracking 2	Yes
Active Gatekeeper	Yes
Traffic Counting	Yes
Pedestrian Counting	Yes

Note: Configurable alerts can be set up for any analytics triggers

ENVIRONMENTAL
<p>Directives:</p> <p>2014/30/EU - Electro Magnetic Compatibility Directive (EMC 2016)</p> <p>2011/305/EU - Construction Products Regulations 2013</p> <p>SI 2005 NO 1803 - General Product Safety Regulations 2005</p> <p>Standards:</p> <p>BS EN 50293 - Electromagnetic Compatibility Road Traffic Signal Systems Product Standard</p> <p>IEC 61215, IEC 61730 and IEC 61701 Certified Solar Panel</p>

ADDITIONAL INFORMATION
All Event CCTV units are deployed with an integrated hand winch (inc. box cover) with a removeable handle
Access the SRL Control Hub via desktop or mobile to see the camera's live feed and analytics data
Multi-screen control centre setup (suitable for events) available to help monitor multiple cameras in one place. Enquire with the team.

AVAILABLE TO HIRE OR PURCHASE

E cctv@srl.co.uk T 0808 2818 775 W srl.co.uk